




GENERAL SPECIFICATIONS

SECTOR SIMPLEX MULTI-BLADE ROTARY SLICERS

| SPECIFICATIONS |  Sector Simplex |  Sector Simplexmatic 250/1 |  Sector Simplexmatic 250/2 |
|--|--|---|---|
| Maximum Output Capacity (Kg & Lbs / hour) | 1,400/ 3,100 | 1,400/ 3,100 | 2,100 / 4,500 |
| Maximum Product Width (mm) | 400 | 400 | 500 |
| Maximum Product Height (mm) | 140 | 140 | 140 |
| Circular Blade Diameter (mm) | 300 | 300 | 300 |
| Power (kW) | 3 | 5.5 | 3 |
| Voltage Requirements | 220/3ph | 220/3ph | 220/3ph |
| Machine Footprint: L x W (mm) | 2,600 x 1130 | 2,600 x 1130 | 2,600 x 1230 |
| Machine Weight (kg) | 500 | 560 | 510 |
| FEATURES | | | |
| Bacteria Proof AISI 304 Stainless Steel Construction | Std | Std | Std |
| Full Magnetic Safety & Security System | Std | Std | Std |
| Low Voltage Electronic Controls | Std | Std | Std |
| Infeed Conveyor | n/a | Std | Std |
| Outfeed Conveyor | n/a | n/a | Std |
| Blade Set Extraction Stand | Std | Std | Std |
| Stainless Steel Blade Set Protective Cover | Std | Std | Std |
| “Plug N’ Play” Design | Std | Std | Std |
| “60 Second” Blade Set Changeover | Std | Std | Std |
| Locking Wheel System | Std | Std | Std |
| No Tool Requirement For Inspection Or Cleaning | Std | Std | Std |
| Blade Pulsing | Std | Std | Std |
| Automatic Washing System | Opt | Opt | Opt |
| Additional Blade Sets From “6mm to 48mm” | Opt | Opt | Opt |
| Blade Set Extraction Stand For Additional Blade Set(s) | Opt | Opt | Opt |
| Vertical Infeed Conveyor System | Opt | Opt | Opt |
| Butterfly Blade Sets | Opt | Opt | Opt |
| Adjustable Product Side Guide | Opt | Opt | Opt |